

INDUSTRIAL COMPONENT DATA

NZMS2-VX40 192035 EATON ELECTRIC Automatic int. NZM2 PXR20, 3p, 40A, screw terminal

Brand: EATON - MOELLER | Manufacturer Part Number: NZMS2-VX40



Manufacturer	EATON - MOELLER
MPN / Reference	NZMS2-VX40
Catalog number	192035
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-ED9EBF5BF7
Generated	2026-08-03

Product Overview

Automatic int. NZM2 PXR20, 3p, 40A, screw terminal

Circuit-breaker, NZM2 PXR20, 3 pole, 40A, screw terminal

The xEffect NZM...-VX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Circuit-breaker, NZM2 PXR20, 3 pole, 40A, screw terminalThe xEffect NZM...-VX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection with only four compact sizes and is suitable for the IEC market. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. R.m.s. value measurement and thermal memory.Delivery program

Product rangeCircuit-breakerProtective functionSystems, cable, selectivity and generator protectionStandard/ApprovalIECInstallation typeFixedRelease systemElectronic releaseConstruction sizeNZM2DescriptionLSI overload protection and delayed and non-delayed short-circuit protective device R.m.s. value measurement and "thermal memory" USB interface for configuration and test function with Power Xpert Protection Manager software

Optionally communication-capable with interface module and internal Modbus RTU module or CAM
Number of poles3
poleStandard equipmentScrew connectionSwitching capacity400/415 V 50 Hz [Icu]70 kARated current = rated uninterrupted
current [In= Iu]Rated current = rated uninterrupted current [In= Iu]40 ASetting rangeOverload trip[Ir]20 - 40 AShort-circuit
releases[Irm]Non-delayed[Ii= Inx ...]2 - 18Short-circuit releases[Irm]Delayed[Isd= Irx ...]2 - 10Technical data
GeneralStandardsIEC/EN 60947Protection against direct contactFinger and back of hand pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZMS2-VX40 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.