

INDUSTRIAL COMPONENT DATA

T0-1-8/Z 009389 Y7-9389 EATON ELECTRIC ON-OFF button, Contacts: 2, 20 A, front plate: 0 1, 45 °, momentary, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-8/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-8/Z
Catalog number	Y7-9389
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-0A90138375
Generated	2026-08-05

Product Overview

ON-OFF button, Contacts: 2, 20 A, front plate: 0 >< 1, 45 °, momentary, rear mounting

Push-button switch ON-OFF; 2-pole; 20a; rating Plate: 0 >< 1; 45 °; Return; Mounting bottom panel

Eaton Moeller® series T0 ON-OFF button, T0, 20 A, rear mounting, 1 contact unit(s), Contacts: 2, 45 °, momentary, With 0 (Off) position, with spring-return from both directions, 0 >< 1, Design number 8

ON OFF button, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: momentary, With 0 (Off) position, with spring-return from both directions, 1 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0 >< 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Accessory ON OFF button Catalog Number 009389 Model Code T0-1-8/Z EAN 4015080093893 Product Length/Depth 118 mm Product Height 48 mm Product Width 48 mm Product Weight 0.112 kg

Certifications CSA

IEC/EN 60204

UL File No.: E36332

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

IEC/EN 60947-3

VDE 0660

UL 60947-4-1

CE

UL Category Control No.: NLRV

CSA-C22.2 No. 94

UL

CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 009389 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

2

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-8/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.