

INDUSTRIAL COMPONENT DATA

T0-6-8348/EZ 088711 Y7-88711 EATON ELECTRIC On-Off switch, 12-pole, 20 A, 90 °, centre mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-8348/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-8348/EZ
Catalog number	Y7-88711
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-23867179D9
Generated	2026-08-06

Product Overview

On-Off switch, 12-pole, 20 A, 90 °, centre mounting

ON-OFF disconnect switch. 12 poles. 20 A. 90°. Flush mounting

On-Off switch, T0, 20 A, centre mounting, 6 contact unit(s), 12-pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: T0, with black thumb grip and front plate, 12-pole, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, T0, 20 A, centre mounting, 6 contact unit(s), 12-pole, with black thumb grip and front plate
On-Off switch, Product range: On-Off switch, Part group reference: T0, with black thumb grip and front plate, 12-pole, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series T0 On-Off switchPart

no.T0-6-8348/EZEAN4015080887119Product Length/Depth144 millimetreProduct height48 millimetreProduct width48 millimetreProduct weight0.24 kilogramCertificationsCE
CSA File No.: 012528

UL

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

CSA

CSA Class No.: 3211-05

UL File No.: E36332

VDE 0660

IEC/EN 60947

UL 60947-4-1

IEC/EN 60204

CSA-C22.2 No. 94Product TradenameT0Product TypeOn-Off switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFitted with:Black thumb grip and front plateInscription0-1Number of poles12General informationDegree of protectionNEMA 12Degree of protection (front side)IP65Lifespan, mechanical400,000 OperationsMounting methodCenter mountingMounting positionAs requiredNumber of contact units6Operating frequency1200 Operations/hOv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-8348/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.