

INDUSTRIAL COMPONENT DATA

T3-1-8200/Z 071327 Y7-71327 EATON ELECTRIC On-Off switch, 1 pole, 32 A, 90 °, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T3-1-8200/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-1-8200/Z
Catalog number	Y7-71327
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5AF3D4CB80
Generated	2026-08-06

Product Overview

On-Off switch, 1 pole, 32 A, 90 °, rear mounting

ON-OFF Disconnect Switch 1 Pole 32 A 90° Panel Bottom Mount

Eaton Moeller® series T3 On-Off switch, T3, 32 A, rear mounting, 1 contact unit(s), 1 pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: T3, with black thumb grip and front plate, 1 pole, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 On-off switch Catalog Number 071327 Model Code T3-1-8200/Z EAN

4015080713272 Product Length/Depth 121 mm Product Height 54 mm Product Width 61 mm Product Weight 0.147 kg

Certifications CSA

CE

UL

CSA Class No.: 3211-07

IEC/EN 60204

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CSA File No.: 012528

CSA-C22.2 No. 94

VDE 0660

UL 60947-4-1

IEC/EN 60947-3

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 071327 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

11 kW

Rated short-time withstand current I_{cw} (EF007050)

0.65 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current I_q (EF001444)

1 kA

Number of poles (EF001391)

1

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as ch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-1-8200/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.