

INDUSTRIAL COMPONENT DATA

T0-1-102/XZ 005736 Y7-5736 EATON ELECTRIC On-Off switch, 2 pole, 20 A, 90 °, rear mounting, Basic switch

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-102/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-102/XZ
Catalog number	Y7-5736
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-F10B928AC2
Generated	2026-08-05

Product Overview

On-Off switch, 2 pole, 20 A, 90 °, rear mounting, Basic switch

ON-OFF 2-Pole Disconnecter Switch 20 A 90° Switch

On-Off switch, T0, 20 A, rear mounting, Basic switch, 1 contact unit(s), 2 pole

On-Off switch, Product range: On-Off switch, Part group reference: T0, 2 pole, Design: rear mounting, Basic switch,

Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

EL-Nummer (Norway)1456651On-Off switch, T0, 20 A, rear mounting, Basic switch, 1 contact unit(s), 2 poleOn-Off switch,

Product range: On-Off switch, Part group reference: T0, 2 pole, Design: rear mounting, Basic switch, Switching angle: 90 °,

Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 1 contact unit(s), Standards:

IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeOn-Off switchPart group referenceT0Number of poles2 poleDesignrear mounting

Basic switchContact sequenceSwitching angle90 °Design number102Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400

V [P]5.5 kWRated uninterrupted current [I_u]20 ANote on rated uninterrupted current I_uRated uninterrupted current I_{uis}

specified for max. cross-section.Number of contact units1 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Mechanical variables Number of poles 2 pole Electrical characteristics Rated operational voltage [Ue] 690 V AC Electrical characteristics Rated uninterrupted current [Iu] 20 A Electrical characteristics Note o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-102/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.