

INDUSTRIAL COMPONENT DATA

T0-2-10/E-RT 011099 Y7-11099 EATON ELECTRIC On-Off switch, 3 pole + N, 20 A, Emergency-Stop function, 90 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-10/E-RT



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-10/E-RT
Catalog number	Y7-11099
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-628D66261E
Generated	2026-08-02

Product Overview

On-Off switch, 3 pole + N, 20 A, Emergency-Stop function, 90 °, flush mounting

Disconnect switch ON-OFF; 3-pole + N; 20 A; Handle, Red/Yellow; 90 °; Mounting

Eaton Moeller® series T0 On-Off switch, 3 pole + N, 20 A, Emergency-Stop function, 90 °, flush mounting T0-2-10/E-RT

On-Off switch, Product range: On-Off switch, Part group reference: T0, Stop Function: Emergency switching off function, with red thumb grip and yellow front plate, 3 pole + N, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On-off switch Catalog Number 011099 Model Code T0-2-10/E-RT EAN 4015080110996 Product Length/Depth 86 mm Product Height 48 mm Product Width 48 mm Product Weight 0.108 kg

Certifications IEC/EN 60947

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

VDE 0660

UL 60947-4-1

CSA File No.: 012528

CSA

UL File No.: E36332

CSA Class No.: 3211-05

UL

CE

IEC/EN 60947-3

CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 011099 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

20 A

Rated permanent current at AC-21, 400 V (EF009165)

20 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Rated short-time withstand current Icw (EF007050)

0.32 kA

Rated operation power at AC-23, 400 V (EF007027)

5.5 kW

Switching power at 400 V (EF009166)

5.5 kW

Conditioned rated short-circuit current Iq (EF001444)

6 kA

Number of poles (EF001391)

4

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-10/E-RT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.