

INDUSTRIAL COMPONENT DATA

P3-100/Z 090931 Y7-90931 EATON ELECTRIC On-Off switch, 3 pole, 100 A, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P3-100/Z



Manufacturer	EATON - MOELLER
MPN / Reference	P3-100/Z
Catalog number	Y7-90931
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-73BA8B6306
Generated	2026-08-03

Product Overview

On-Off switch, 3 pole, 100 A, rear mounting

ON-OFF 3-pole disconnecter switch 100 A Panel Bottom Mount

Eaton Moeller® series P3 On-Off switch, P3, 100 A, rear mounting, 3 pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: P3, with black thumb grip and front plate, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 On-off switch Catalog Number 090931 Model Code P3-100/Z EAN

4015080909316 Product Length/Depth 150 mm Product Height 114 mm Product Width 90 mm Product Weight 0.36 kg

Certifications UL 60947-4-1

UL Category Control No.: NLRV

CSA

CSA Class No.: 3211-05

IEC/EN 60947-3

IEC/EN 60947

UL File No.: E36332
VDE 0660
CSA File No.: 012528
CSA-C22.2 No. 60947-4-1-14
CE
IEC/EN 60204
CSA-C22.2 No. 94
UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 090931 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
100 A
Rated permanent current at AC-23, 400 V (EF011777)
100 A
Rated permanent current at AC-21, 400 V (EF009165)
100 A
Rated operation power at AC-3, 400 V (EF001364)
37 kW
Rated short-time withstand current I_{cw} (EF007050)
2 kA
Rated operation power at AC-23, 400 V (EF007027)
55 kW
Switching power at 400 V (EF009166)
55 kW
Conditioned rated short-circuit current I_q (EF001444)
80 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF00137...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-100/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.