

INDUSTRIAL COMPONENT DATA

P5-250/E 280935 Y7-280935 EATON ELECTRIC On-Off switch, 3 pole, 250 A, flush mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P5-250/E



Manufacturer	EATON - MOELLER
MPN / Reference	P5-250/E
Catalog number	Y7-280935
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-67D3AE1A73
Generated	2026-08-04

Product Overview

On-Off switch, 3 pole, 250 A, flush mounting

P5-250/E

On-Off switch, P5, 250 A, flush mounting, 3 pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: P5, with black thumb grip and front plate, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 90 kW, Rated uninterrupted current: I_u = 250 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, P5, 250 A, flush mounting, 3 pole, with black thumb grip and front plateOn-Off switch, Product range: On-Off switch, Part group reference: P5, with black thumb grip and front plate, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 90 kW, Rated uninterrupted current: I_u = 250 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series P5 On-Off switchPart no.P5-250/EEAN4015082809355Product Length/Depth150 millimetreProduct height150 millimetreProduct width130 millimetreProduct weight1.865 kilogramCompliancesCE MarkedCertificationsUL 508 IEC 60947

EN 60947-3

CSA Std. C22.2 No. 14-05

VDE

CE

CSA File No.: 223805

UL File No.: E36332

IEC/EN 60947

UL Category Control No.: NLRV

IEC/EN 60947-3

UL

CSA

VDE 0660

CSA-C22.2 No. 94

CSA Class No.: 3211-05

IEC/EN 60204

CSA-C22.2 No. 14-05

CSA

ULProduct TradenameP5Product TypeOn-Off switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFitted with:Black thumb grip and front plateNumber of poles3General informationAccessoriesAuxiliary contact or neutral conductor fitted by user.Degree of protectionNEMA 12Degree of protection (front side)IP65Lifespan, mechanical80,000 OperationsMounting methodFlush mountingMo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P5-250/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.