

INDUSTRIAL COMPONENT DATA

P1-25/E/SVA(A) 050965 Y7-50965 EATON ELECTRIC ON-OFF switches, 3 pole, 25 A, Cylinder lock SVA, flush mounti..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/E/SVA(A)



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/E/SVA(A)
Catalog number	Y7-50965
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-72BF8C38BD
Generated	2026-08-05

Product Overview

ON-OFF switches, 3 pole, 25 A, Cylinder lock SVA, flush mounting, P

ON-OFF disconnect switch. 3 poles. 25 A. Cylinder lock SVA.

Eaton Moeller® series P1 ON-OFF switches, P1, 25 A, flush mounting, 3 pole, with black thumb grip and front plate, Cylinder lock SVA

On-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method: Flush mounting, Number of poles: Three-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 050965 Model Code P1-25/E/SVA(A) EAN 4015080509653 Product Length/Depth 139 mm Product Height 73 mm Product Width 49 mm Product Weight 0.268 kg

Certifications IEC/EN 60947-3

IEC/EN 60204

IEC/EN 60947

VDE 0660

ETIM for 050965 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

25 A

Rated permanent current at AC-23, 400 V (EF011777)

25 A

Rated permanent current at AC-21, 400 V (EF009165)

25 A

Rated operation power at AC-3, 400 V (EF001364)

7.5 kW

Rated short-time withstand current I_{cw} (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

13 kW

Switching power at 400 V (EF009166)

13 kW

Conditioned rated short-circuit current I_q (EF001444)

80 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optiona...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/E/SVA(A) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.