

INDUSTRIAL COMPONENT DATA

P1-25/Z 057708 Y7-57708 EATON ELECTRIC On-Off switch, 3 pole, 25 A, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/Z



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/Z
Catalog number	Y7-57708
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-DE5B7E0DA5
Generated	2026-08-05

Product Overview

On-Off switch, 3 pole, 25 A, rear mounting

ON-OFF 3-pole disconnecter switch 25 A Panel Bottom Mount

On-Off switch, P1, 25 A, rear mounting, 3 pole, with black thumb grip and front plate

On-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method:

Rear mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, P1, 25 A, rear mounting, 3 pole, with black thumb grip and front plateOn-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method: Rear mounting, Number of poles:

Three-pole, Degree of Protection: NEMA 12

General specificationsProduct nameEaton Moeller® series P1 On-Off switchPart no.P1-25/ZEAN4015080577089Product Length/Depth131 millimetreProduct height70 millimetreProduct width49 millimetreProduct weight0.131

kilogramCertificationsCE

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

IEC/EN 60947

UL

CSA File No.: 012528

CSA

CSA-C22.2 No. 94

IEC/EN 60204

UL Category Control No.: NLRV

UL 60947-4-1

CSA Class No.: 3211-05

VDE 0660

IEC/EN 60947-3Product TradenameP1Product TypeOn-Off switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFitted with:Black thumb grip and front plateNumber of poles3General informationAccessoriesAuxiliary contact or neutral conductor fitted by user.Degree of protectionNEMA 12Degree of protection (front side)IP65Lifespan, mechanical300,000 OperationsMounting methodRear mountingMounting positionAs requiredOperating frequency1200 Operations/hOvervoltage categoryIIIPollution degree3Rated impulse withstand voltage (Uimp)6000 V ACsafe isolation440 V AC, Between the contacts, According to EN 61140Safety parameter (EN ISO 13849-1)B10d values as per EN ISO 13849-1, table C.1Shock resistance15 g, Mechanical, According to...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.