

INDUSTRIAL COMPONENT DATA

P1-32/E 079065 Y7-79065 EATON ELECTRIC On-Off switch, 3 pole, 32 A, flush mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/E



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/E
Catalog number	Y7-79065
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-22761E870D
Generated	2026-07-29

Product Overview

On-Off switch, 3 pole, 32 A, flush mounting

ON-OFF 3-pole disconnecter switch 32 A Flush Mount

Eaton Moeller® series P1 On-Off switch, P1, 32 A, flush mounting, 3 pole, with black thumb grip and front plate

On-Off switch, P1, Rated uninterrupted current (Iu): 32 A, Fitted with: Black thumb grip and front plate, Mounting method:

Flush mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch

Catalog Number 079065

Model Code P1-32/E

EAN 4015080790655

Product Length/Depth 95 mm

Product Height 70 mm

Product Width 49 mm

Product Weight 0.143 kg

Certifications CE

CSA Class No.: 3211-05

CSA-C22.2 No. 94

CSA

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

VDE 0660

CSA File No.: 012528

IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204

UL

UL Category Control No.: NLRV

Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

Features & Functions

Fitted with: Black thumb grip and front plate

Number of poles 3

General information

Accessories Auxiliary contact or neutral conductor fitted by user.

Degree of protection NEMA 12

Degree of protection (front side) IP65

Lifespan, mechanical 300,000 Operations

Mounting method Flush mounting

Mounting position As required

Operating frequency 1200 Operations/h

Overvoltage category III

Pollution degree 3

Product Category On-Off switch

Product Category On-Off switch

Rated impulse withstand voltage (U_{imp}) 6000 V AC

Safe isolation 440 V AC, Between the contacts, According to EN 61140

Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

Suitable for Front mounting 4-hole

Branch circuits, suitable as motor disconnect, (UL/CSA)

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.