

INDUSTRIAL COMPONENT DATA

P1-32/XZ 046304 Y7-46304 EATON ELECTRIC On-Off switch, 3p, 32A, replacement switch

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/XZ
Catalog number	Y7-46304
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-B3AF78BDAF
Generated	2026-08-01

Product Overview

On-Off switch, 3p, 32A, replacement switch

ON-OFF 3-pole disconnecter switch 32 A Replacement switch

Basic switch, Product range: Main switch, maintenance switch, Part group reference: P1, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Design: Basic switch, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, 3p, 32A, replacement switchBasic switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: P1, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Design: Basic switch, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program Product rangeMain switch maintenance switch

Repair switchPart group referenceP1Information about equipment suppliedAuxiliary contact or neutral conductor fitted by user.Number of poles3 poleAuxiliary contacts0 N/O0 N/CDesignBasic switchContact sequenceFront plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [I_u]32 ANote on rated uninterrupted current !uRated uninterrupted current I_u is specified for max. cross-section.Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +50 °C Ambient temperature Enclosed -25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock

resistance 15 g Mounting position As required Contacts Mechanical variables Number of poles 3 pole Mechanical

variables Auxiliary contacts 0 N/O Mechanical variables Auxiliary contacts 0 N/C Electri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.