

INDUSTRIAL COMPONENT DATA

T0-2-1/Z 036504 Y7-36504 EATON ELECTRIC On-Off switch, 3 pole, 20 A, 90 °, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-1/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-1/Z
Catalog number	Y7-36504
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-FA6DB7775B
Generated	2026-08-06

Product Overview

On-Off switch, 3 pole, 20 A, 90 °, rear mounting

ON-OFF disconnect switch. 3 poles. 20 A. 90°. Panel bottom mounting

Eaton Moeller® series T0 On-Off switch, T0, 20 A, rear mounting, 2 contact unit(s), 3 pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: T0, with black thumb grip and front plate, 3 pole, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On-off switch

Catalog Number 036504

Model Code T0-2-1/Z

EAN 4015080365044

Product Length/Depth 128 mm

Product Height 48 mm

Product Width 48 mm

Product Weight 0.134 kg

Certifications CE

IEC/EN 60947

IEC/EN 60947-3

VDE 0660

CSA-C22.2 No. 94

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

UL 60947-4-1

CSA File No.: 012528

UL File No.: E36332

IEC/EN 60204

UL Category Control No.: NLRV

UL

CSA

Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

Features & Functions

Fitted with: Black thumb grip and front plate

Inscription 0-1

Number of poles 3

General information

Degree of protection NEMA 12

Degree of protection (front side) IP65

Lifespan, mechanical 400,000 Operations

Mounting method Rear mounting

Mounting position As required

Number of contact units 2

Operating frequency 1200 Operations/h

Overvoltage category III

Pollution degree 3

Product Category On-Off switch

Product Category On-Off switch

Rated impulse withstand voltage (Uimp) 6000 V AC

Safe isolation 440 V AC, Between the contacts, According to EN 61140

Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

Suitable for Ground mounting

Intermediate mounting

Branch circuits, suitable as motor disconnect, (UL/CSA)

Switching angle 90 °

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient ope...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-1/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.