

INDUSTRIAL COMPONENT DATA

T0-2-15679/XZ 011459 Y7-11459 EATON ELECTRIC On-Off switch, 3 pole + 1 N/O, 20 A, 90 °, rear mounting, Basic..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15679/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15679/XZ
Catalog number	Y7-11459
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-F5393995F9
Generated	2026-08-04

Product Overview

On-Off switch, 3 pole + 1 N/O, 20 A, 90 °, rear mounting, Basic switch

ON-OFF Disconnect Switch 3 Poles + 1 NO 20 A 90° Switch

On-Off switch, T0, 20 A, rear mounting, Basic switch, 2 contact unit(s), 3 pole, 1 N/O

On-Off switch, Product range: On-Off switch, Part group reference: T0, 3 pole, Design: rear mounting, Basic switch, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

On-Off switch, T0, 20 A, rear mounting, Basic switch, 2 contact unit(s), 3 pole, 1 N/OOn-Off switch, Product range: On-Off switch, Part group reference: T0, 3 pole, Design: rear mounting, Basic switch, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeOn-Off switchPart group referenceT0Number of poles3 poleAuxiliary contacts1 N/O0 N/CDesignrear mounting

Basic switchContact sequenceSwitching angle90 °Design number15679Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted current [I_u]20 ANote on rated uninterrupted current I_uRated uninterrupted current I_u is specified for max. cross-section.Number of contact units2 contact unit(s)Technical data GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40
°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock
resistance15 gMounting positionAs requiredContactsMechanical variablesNumber of poles3 poleMechanical
variablesAuxiliary contacts1 N/OMechanical variablesAuxiliary contacts0 N/CElectrical characteristicsRated operational
voltage [Ue]690....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15679/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.