

INDUSTRIAL COMPONENT DATA

P3-100/E/HI11 069574 Y7-69574 EATON ELECTRIC On-Off switch, 3 pole + 1 N/O + 1 N/C, 100 A, flush mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P3-100/E/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P3-100/E/HI11
Catalog number	Y7-69574
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-AE3C7A2F82
Generated	2026-08-04

Product Overview

On-Off switch, 3 pole + 1 N/O + 1 N/C, 100 A, flush mounting

ON-OFF disconnecter switch 3 poles + 1 NO + 1 NC 100 A Mounting

On-Off switch, P3, 100 A, flush mounting, 3 pole, 1 N/O, 1 N/C, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: P3, with black thumb grip and front plate, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, P3, 100 A, flush mounting, 3 pole, 1 N/O, 1 N/C, with black thumb grip and front plate
On-Off switch, Product range: On-Off switch, Part group reference: P3, with black thumb grip and front plate, Information about equipment supplied: Auxiliary contact or neutral conductor fitted by user., 3 pole, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specifications
Product name Eaton Moeller® series P3 On-Off switch
Part

no. P3-100/E/HI11
EAN 4015080695745
Product Length/Depth 100 millimetre
Product height 90 millimetre
Product width 90 millimetre
Product weight 0.37 kilogram
Certifications CE
UL

IEC/EN 60204

UL Category Control No.: NLRV

IEC/EN 60947

UL File No.: E36332

CSA-C22.2 No. 94

UL 60947-4-1

CSA

CSA-C22.2 No. 60947-4-1-14

VDE 0660

CSA File No.: 012528

IEC/EN 60947-3

CSA Class No.: 3211-05

UL

CSA Product Tradename P3 Product Type On-Off switch Product Sub Type None Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second Features & Functions Fitted with: Black thumb grip and front plate Number of poles 3 General information Accessories Auxiliary contact or neutral conductor fitted by user. Degree of protection NEMA 12 Degree of protection (front side) IP65 Lifespan, mechanical 100,000 Operations Mounting method Flush mounting Mounting position As required Operating freq...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-100/E/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.