

INDUSTRIAL COMPONENT DATA

P1-25/EZ/HI11 048371 Y7-48371 EATON ELECTRIC On-Off switch, 3 pole + 1 N/O + 1 N/C, 25 A, centre mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/EZ/HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/EZ/HI11
Catalog number	Y7-48371
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-6490E93E49
Generated	2026-08-06

Product Overview

On-Off switch, 3 pole + 1 N/O + 1 N/C, 25 A, centre mounting

Disconnecter switch ON-OFF; 3 poles + 1 NO + 1 NC; 25 A; Assembly

Eaton Moeller® series P1 On-Off switch, P1, 25 A, centre mounting, 3 pole, 1 N/O, 1 N/C, with black thumb grip and front plate

On-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method: Center mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 048371 Model Code P1-25/EZ/HI11 EAN 4015080483717 Product Length/Depth 99 mm Product Height 70 mm Product Width 64 mm Product Weight 0.192 kg

Certifications CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

VDE 0660

CSA Class No.: 3211-05

CE

CSA

IEC/EN 60947-3

CSA-C22.2 No. 94
UL File No.: E36332
CSA File No.: 012528
IEC/EN 60204
UL 60947-4-1
IEC/EN 60947
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 048371 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
25 A
Rated permanent current at AC-23, 400 V (EF011777)
25 A
Rated permanent current at AC-21, 400 V (EF009165)
25 A
Rated operation power at AC-3, 400 V (EF001364)
7.5 kW
Rated short-time withstand current Icw (EF007050)
0.64 kA
Rated operation power at AC-23, 400 V (EF007027)
13 kW
Switching power at 400 V (EF009166)
13 kW
Conditioned rated short-circuit current Iq (EF001444)
80 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/EZ/HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.