

INDUSTRIAL COMPONENT DATA

P1-25/EZ/2HI11 012395 Y7-12395 EATON ELECTRIC On-Off switch, 3 pole + 2 N/O + 2 N/C, 25 A, centre mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/EZ/2HI11



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/EZ/2HI11
Catalog number	Y7-12395
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5641A86A67
Generated	2026-08-05

Product Overview

On-Off switch, 3 pole + 2 N/O + 2 N/C, 25 A, centre mounting

ON-OFF disconnecter switch 3 poles + 2 NO + 2 NC 25 A Mounting

Eaton Moeller® series P1 On-Off switch, P1, 25 A, centre mounting, 3 pole, 2 N/O, 2 N/C, with black thumb grip and front plate

On-Off switch, P1, Rated uninterrupted current (Iu): 25 A, Fitted with: Black thumb grip and front plate, Mounting method: Center mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 012395 Model Code P1-25/EZ/2HI11 EAN 4015080123958 Product Length/Depth 99 mm Product Height 70 mm Product Width 79 mm Product Weight 0.232 kg Certifications CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

CE

UL File No.: E36332

UL Category Control No.: NLRV

IEC/EN 60947

IEC/EN 60947-3

VDE 0660

IEC/EN 60204

UL

CSA File No.: 012528

CSA Class No.: 3211-05

CSA-C22.2 No. 94

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 012395 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

25 A

Rated permanent current at AC-23, 400 V (EF011777)

25 A

Rated permanent current at AC-21, 400 V (EF009165)

25 A

Rated operation power at AC-3, 400 V (EF001364)

7.5 kW

Rated short-time withstand current Icw (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

13 kW

Switching power at 400 V (EF009166)

13 kW

Conditioned rated short-circuit current Iq (EF001444)

80 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/EZ/2HI11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.