

INDUSTRIAL COMPONENT DATA

P3-100/Z/N 038878 Y7-38878 EATON ELECTRIC On-Off switch, 3 pole + N, 100 A, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P3-100/Z/N



Manufacturer	EATON - MOELLER
MPN / Reference	P3-100/Z/N
Catalog number	Y7-38878
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-A8F9CF67B7
Generated	2026-08-05

Product Overview

On-Off switch, 3 pole + N, 100 A, rear mounting

ON-OFF 3-pole + N 100 A disconnecter switch Bottom Panel Mount

Eaton Moeller® series P3 On-Off switch, P3, 100 A, rear mounting, 3 pole + N, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: P3, with black thumb grip and front plate, Information about equipment supplied: auxiliary contact fitted by user., 3 pole + N, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P3 On-off switch Catalog Number 038878 Model Code P3-100/Z/N EAN

4015080388784 Product Length/Depth 150 mm Product Height 114 mm Product Width 90 mm Product Weight 0.43 kg

Certifications CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

VDE 0660

CSA

CE

UL

UL 60947-4-1
CSA File No.: 012528
IEC/EN 60204
CSA Class No.: 3211-05
IEC/EN 60947-3
CSA-C22.2 No. 94
UL Category Control No.: NLRV
UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 038878 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
100 A
Rated permanent current at AC-23, 400 V (EF011777)
100 A
Rated permanent current at AC-21, 400 V (EF009165)
100 A
Rated operation power at AC-3, 400 V (EF001364)
37 kW
Rated short-time withstand current I_{cw} (EF007050)
2 kA
Rated operation power at AC-23, 400 V (EF007027)
55 kW
Switching power at 400 V (EF009166)
55 kW
Conditioned rated short-circuit current I_q (EF001444)
80 kA
Number of poles (EF001391)
4
Number of auxiliary contacts as normally closed contact (EF001...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P3-100/Z/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.