

## INDUSTRIAL COMPONENT DATA

# P1-32/E/N 093456 Y7-93456 EATON ELECTRIC On-Off switch, 3 pole + N, 32 A, flush mounting

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/E/N



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | P1-32/E/N           |
| Catalog number  | Y7-93456            |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-7F098EFFFFB      |
| Generated       | 2026-08-02          |

## Product Overview

On-Off switch, 3 pole + N, 32 A, flush mounting

ON-OFF 3-pole + N 32 A disconnecter switch Flush mount

Eaton Moeller® series P1 On-Off switch, P1, 32 A, flush mounting, 3 pole + N, with black thumb grip and front plate

On-Off switch, P1, Rated uninterrupted current (Iu): 32 A, Fitted with: Black thumb grip and front plate, Mounting method:

Flush mounting, Number of poles: Four-pole, Degree of Protection: NEMA 12

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 093456 Model Code P1-32/E/N EAN

4015080934561 Product Length/Depth 95 mm Product Height 70 mm Product Width 65 mm Product Weight 0.173 kg

Certifications CSA

CSA-C22.2 No. 94

UL Category Control No.: NLRV

CSA File No.: 012528

CSA Class No.: 3211-05

IEC/EN 60947

VDE 0660

CE

UL

UL File No.: E36332

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 093456 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage U<sub>e</sub> AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current I<sub>u</sub> (EF001389)

32 A

Rated permanent current at AC-23, 400 V (EF011777)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

13 kW

Rated short-time withstand current I<sub>cw</sub> (EF007050)

0.64 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current I<sub>q</sub> (EF001444)

80 kA

Number of poles (EF001391)

4

Number of auxiliary contacts as normally closed contact (EF00137...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/E/N with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.