

INDUSTRIAL COMPONENT DATA

P1-32/IVS/N 010402 Y7-10402 EATON ELECTRIC On-Off switch, 3 pole + N, 32 A, service distribution board mount..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/IVS/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/IVS/N
Catalog number	Y7-10402
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-4790B1229D
Generated	2026-08-03

Product Overview

On-Off switch, 3 pole + N, 32 A, service distribution board mounting

ON-OFF 3-pole + N 32 A disconnecter switch

On-Off switch, P1, 32 A, service distribution board mounting, 3 pole + N, with black thumb grip and front plate

On-Off switch, P1, Rated uninterrupted current (Iu): 32 A, Fitted with: Black thumb grip and front plate, Mounting method:

Service distribution board mounting, Number of poles: Four-pole, Degree of Protection: NEMA Other

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, P1, 32 A, service distribution board mounting, 3 pole + N, with black thumb grip and front plate
On-Off switch, P1, Rated uninterrupted current (Iu): 32 A, Fitted with: Black thumb grip and front plate, Mounting method: Service distribution board mounting, Number of poles: Four-pole, Degree of Protection: NEMA Other

General specifications
Product name Eaton Moeller® series P1 On-Off switch
Part

no. P1-32/IVS/NEAN4015080104025
Product Length/Depth 90 millimetre
Product height 70 millimetre
Product width 63 millimetre
Product weight 0.183 kilogram
Certifications UL Category Control No.: NLRV

UL

IEC/EN 60947-3

CSA-C22.2 No. 94

CSA File No.: 012528

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

IEC/EN 60204

CE

CSA

IEC/EN 60947

CSA Class No.: 3211-05

VDE 0660Product TradenameP1Product TypeOn-Off switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFitted with:Black thumb grip and front plateNumber of poles4General informationAccessoriesAuxiliary contact fitted by user.Degree of protectionNEMA OtherDegree of protection (front side)IP30Lifespan, mechanical300,000 OperationsMounting methodService distribution board mountingMounting positionAs requiredOperating frequency1200 Operations/hOvervoltage categoryIIIPollution degree3Rated impulse withstand voltage (Uimp)6000 V ACsafe isolation440 V AC, Between the contacts, According to EN 61140Safety parameter (EN ISO 13849-1)B10d values as per EN ISO 13849-1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/IVS/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.