

INDUSTRIAL COMPONENT DATA

T0-2-8900/XZ 226093 Y7-226093 EATON ELECTRIC On-Off switch, 3 pole + N, 20 A, 90 °, rear mounting, Basic swi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8900/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8900/XZ
Catalog number	Y7-226093
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E906F7EF26
Generated	2026-08-05

Product Overview

On-Off switch, 3 pole + N, 20 A, 90 °, rear mounting, Basic switch

T0-2-8900/XZ

On-Off switch, Product range: On-Off switch, Part group reference: T0, 3 pole + N, Design: rear mounting, Basic switch, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, 3 pole + N, 20 A, 90 °, rear mounting, Basic switch
On-Off switch, Product range: On-Off switch, Part group reference: T0, 3 pole + N, Design: rear mounting, Basic switch, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3
Delivery program

Product rangeOn-Off switchPart group referenceT0Number of poles3 pole + NDesignrear mounting

Basic switchContact sequenceSwitching angle90 °Design number8900Front plate no.Motor rating AC-23A, 50 - 60 Hz

[P]400 V [P]5.5 kWRated uninterrupted current [I_u]20 ANote on rated uninterrupted current I_uRated uninterrupted current I_u is specified for max. cross-section.Number of contact units2 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U_{imp}] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Mechanical variables Number of poles 3 pole + N Electrical characteristics Rated operational voltage [U_e] 690 V AC Electrical characteristics Rated uninterrupted current [I_u] 20 A Electrical characteristics Note on rated uninterrupted cur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8900/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.