

INDUSTRIAL COMPONENT DATA

TM-2-8293/IVS 225337 Y7-225337 EATON ELECTRIC ON-OFF switches, Contacts: 4, 10 A, front plate: 0-1, 90 °, ma..

Brand: EATON - MOELLER | Manufacturer Part Number: TM-2-8293/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	TM-2-8293/IVS
Catalog number	Y7-225337
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-6C1E444FB9
Generated	2026-08-05

Product Overview

ON-OFF switches, Contacts: 4, 10 A, front plate: 0-1, 90 °, maintained, service distribution board mounting
TM-2-8293/IVS

Eaton Moeller® series TM ON-OFF switches, TM, 10 A, service distribution board mounting, 2 contact unit(s), Contacts: 4, 90 °, maintained, With 0 (Off) position, 0-1, Design number 8293

On-Off switch, Product range: Control switches, Part group reference: TM, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 3 kW, Rated uninterrupted current: I_u = 10 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, CSA, UL, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series TM On-off switch Catalog Number 225337 Model Code TM-2-8293/IVS EAN 4015082253370 Product Length/Depth 72.5 mm Product Height 60 mm Product Width 35.5 mm Product Weight 0.058 kg

Certifications IEC/EN 60947-3

UL File No.: E36332

UL Category Control No.: NLRV

CSA-C22.2 No. 14-05

UL 508

IEC/EN 60947

VDE 0660

IEC/EN 60947-5-1

CE

UL report applies to both US and Canada

UL

Certified by UL for use in Canada

CSA-C22.2 No. 94

CSA

ETIM for 225337 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

1000 V

Rated permanent current I_u (EF001389)

10 A

Rated permanent current at AC-23, 400 V (EF011777)

6.6 A

Rated permanent current at AC-21, 400 V (EF009165)

0 A

Rated operation power at AC-3, 400 V (EF001364)

0 kW

Rated short-time withstand current I_{cw} (EF007050)

0 kA

Rated operation power at AC-23, 400 V (EF007027)

3 kW

Switching power at 400 V (EF009166)

0 kW

Conditioned rated short-circuit current I_q (EF001444)

0 kA

Number of poles (EF001391)

4

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as cha...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-2-8293/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.