

INDUSTRIAL COMPONENT DATA

T3-2-8324/Z 018500 Y7-18500 EATON ELECTRIC On-Off switch, 4 pole, 32 A, 90 °, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8324/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-8324/Z
Catalog number	Y7-18500
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-9E73FFF48B
Generated	2026-08-06

Product Overview

On-Off switch, 4 pole, 32 A, 90 °, rear mounting

ON-OFF 4-pole disconnecter switch 32 A 90° Panel bottom mount

Eaton Moeller® series T3 On-Off switch, T3, 32 A, rear mounting, 2 contact unit(s), 4 pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: T3, with black thumb grip and front plate, 4 pole, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 On-off switch Catalog Number 018500 Model Code T3-2-8324/Z EAN

4015080185000 Product Length/Depth 133 mm Product Height 54 mm Product Width 61 mm Product Weight 0.195 kg

Certifications CSA Class No.: 3211-05

CSA-C22.2 No. 94

UL

UL File No.: E36332

VDE 0660

IEC/EN 60204
IEC/EN 60947
UL Category Control No.: NLRV
UL 60947-4-1
IEC/EN 60947-3
CE
CSA File No.: 012528
CSA-C22.2 No. 60947-4-1-14
CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 018500 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
32 A
Rated permanent current at AC-21, 400 V (EF009165)
32 A
Rated operation power at AC-3, 400 V (EF001364)
11 kW
Rated short-time withstand current Icw (EF007050)
0.65 kA
Rated operation power at AC-23, 400 V (EF007027)
15 kW
Switching power at 400 V (EF009166)
15 kW
Conditioned rated short-circuit current Iq (EF001444)
1 kA
Number of poles (EF001391)
4
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8324/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.