

## INDUSTRIAL COMPONENT DATA

**TM-3-8326/E 079623 Y7-79623 EATON ELECTRIC ON-OFF switches, Contacts: 6, 10 A, front plate: 0-1, 90 °, maint..**

Brand: EATON - MOELLER | Manufacturer Part Number: TM-3-8326/E



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | TM-3-8326/E         |
| Catalog number  | Y7-79623            |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-DEAEA97AF8       |
| Generated       | 2026-08-04          |

**Product Overview**

ON-OFF switches, Contacts: 6, 10 A, front plate: 0-1, 90 °, maintained, flush mounting

ON-OFF 6-pole disconnect switch 10 A Faceplate 0-1 90°

Eaton Moeller® series TM ON-OFF switches, TM, 10 A, flush mounting, 3 contact unit(s), Contacts: 6, 90 °, maintained, With 0 (Off) position, 0-1, Design number 8326

On-Off switch, Product range: Control switches, Part group reference: TM, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 3 kW, Rated uninterrupted current: I<sub>u</sub> = 10 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, CSA, UL, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

General specifications

Product Name Eaton Moeller® series TM On-off switch Catalog Number 079623 Model Code TM-3-8326/E EAN 4015080796237 Product Length/Depth 86 mm Product Height 30 mm Product Width 30 mm Product Weight 0.05 kg

Certifications IEC/EN 60947-5-1

UL File No.: E36332

VDE 0660

IEC/EN 60947-3

Certified by UL for use in Canada

CSA

CSA-C22.2 No. 94

UL report applies to both US and Canada

CSA-C22.2 No. 14-05

UL 508

IEC/EN 60947

UL

UL Category Control No.: NLRV

CE

ETIM for 079623 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current  $I_u$  (EF001389)

10 A

Rated permanent current at AC-21, 400 V (EF009165)

0 A

Rated operation power at AC-3, 400 V (EF001364)

0 kW

Rated short-time withstand current  $I_{cw}$  (EF007050)

0 kA

Rated operation power at AC-23, 400 V (EF007027)

3 kW

Switching power at 400 V (EF009166)

0 kW

Conditioned rated short-circuit current  $I_q$  (EF001444)

0 kA

Number of poles (EF001391)

6

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-3-8326/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.