

INDUSTRIAL COMPONENT DATA

T5B-4-15682/Z 207429 Y7-207429 EATON ELECTRIC On-Off switch, 6 pole + 1 N/O + 1 N/C, 63 A, 90 °, rear mounti..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-15682/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-4-15682/Z
Catalog number	Y7-207429
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-0064D74ED6
Generated	2026-08-06

Product Overview

On-Off switch, 6 pole + 1 N/O + 1 N/C, 63 A, 90 °, rear mounting

T5B-4-15682/Z

Eaton Moeller® series T5B On-Off switch, 6 pole + 1 N/O + 1 N/C, 63 A, 90 °, rear mounting T5B-4-15682/Z

On-Off switch, Product range: On-Off switch, Part group reference: T5B, with black thumb grip and front plate, 6 pole, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B On-off switch Catalog Number 207429 Model Code T5B-4-15682/Z EAN 4015082074296 Product Length/Depth 182 mm Product Height 88 mm Product Width 88 mm Product Weight 0.769 kg

Certifications CSA

IEC/EN 60204

IEC/EN 60947-3

CSA Class No.: 3211-07

UL

UL Category Control No.: NLRV

CE

CSA-C22.2 No. 60947-4-1-14

VDE 0660

CSA File No.: 012528

CSA-C22.2 No. 94

UL 60947-4-1

IEC/EN 60947

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 207429 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

63 A

Rated permanent current at AC-23, 400 V (EF011777)

63 A

Rated permanent current at AC-21, 400 V (EF009165)

63 A

Rated operation power at AC-3, 400 V (EF001364)

22 kW

Rated short-time withstand current Icw (EF007050)

1.3 kA

Rated operation power at AC-23, 400 V (EF007027)

30 kW

Switching power at 400 V (EF009166)

30 kW

Conditioned rated short-circuit current Iq (EF001444)

2 kA

Number of poles (EF001391)

6

Number of auxiliary contacts as normally closed contact (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-15682/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.