

INDUSTRIAL COMPONENT DATA

T3-4-8344/E 020593 Y7-20593 EATON ELECTRIC On-Off switch, 8-pole, 32 A, 90 °, flush mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-8344/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-8344/E
Catalog number	Y7-20593
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-FCB54108BF
Generated	2026-08-05

Product Overview

On-Off switch, 8-pole, 32 A, 90 °, flush mounting

ON-OFF disconnect switch; 8 poles; 32 A; 90 °; Recessed Mounting

On-Off switch, T3, 32 A, flush mounting, 4 contact unit(s), 8-pole, with black thumb grip and front plate

On-Off switch, Product range: On-Off switch, Part group reference: T3, with black thumb grip and front plate, 8-pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

On-Off switch, T3, 32 A, flush mounting, 4 contact unit(s), 8-pole, with black thumb grip and front plate
On-Off switch, Product range: On-Off switch, Part group reference: T3, with black thumb grip and front plate, 8-pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specifications
Product name Eaton Moeller® series T3 On-Off switch
Part

no. T3-4-8344/EEAN4015080205937
Product Length/Depth 114 millimetre
Product height 54 millimetre
Product width 61 millimetre
Product weight 0.252 kilogram
Certifications UL File No.: E36332
IEC/EN 60947-3

IEC/EN 60947

UL

UL Category Control No.: NLRV

VDE 0660

CSA File No.: 012528

IEC/EN 60204

CSA Class No.: 3211-07

CSA

CSA-C22.2 No. 94

CSA-C22.2 No. 60947-4-1-14

CE

UL 60947-4-1

CSA

ULProduct TradenameT3Product TypeOn-Off switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsFitted with:Black thumb grip and front plateInscription0-1Number of poles8General informationDegree of protectionNEMA 12Degree of protection (front side)IP65Lifespan, mechanical500,000 OperationsMounting methodFlush mountingMounting positionAs requiredNumber of contact units4Operating frequency1200 Operations/hOv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-8344/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.