

INDUSTRIAL COMPONENT DATA

P1-32/I2-RT 207321 Y7-207321 EATON ELECTRIC On-Off switch, 3 pole, 32 A, Emergency-Stop function, surface mo..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-32/I2-RT



Manufacturer	EATON - MOELLER
MPN / Reference	P1-32/I2-RT
Catalog number	Y7-207321
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5C9FF85223
Generated	2026-08-02

Product Overview

On-Off switch, 3 pole, 32 A, Emergency-Stop function, surface mounting

P1-32/I2-RT

Eaton Moeller® series P1 On-Off switch, 3 pole, 32 A, Emergency-Stop function, surface mounting P1-32/I2-RT

On-Off switch, P1, Rated uninterrupted current (Iu): 32 A, Functions: Emergency switching off function, Fitted with: Red thumb grip and yellow front plate, Mounting method: Surface mounting, Number of poles: Three-pole, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 On-off switch Catalog Number 207321 Model Code P1-32/I2-RT EAN

4015082073213 Product Length/Depth 107 mm Product Height 180 mm Product Width 100 mm Product Weight 0.422 kg

Certifications IEC/EN 60947-3

UL

IEC/EN 60204

CSA

VDE 0660

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 207321 Low-voltage industrial controls and switchgear (EC000216)

Feature Name	Feature Value
Version as main switch (EF006981)	No
Version as maintenance-/service switch (EF006986)	No
Version as safety switch (EF006985)	No
Version as emergency stop installation (EF006959)	No
Version as reversing switch (EF009408)	No
Number of switches (EF005586)	1
Max. rated operation voltage Ue AC (EF007355)	690 V
Rated operating voltage (EF001435)	690 V
Rated permanent current Iu (EF001389)	32 A
Rated permanent current at AC-23, 400 V (EF011777)	32 A
Rated permanent current at AC-21, 400 V (EF009165)	32 A
Rated operation power at AC-3, 400 V (EF001364)	13 kW
Rated short-time withstand current Icw (EF007050)	0.64 kA
Rated operation power at AC-23, 400 V (EF007027)	15 kW
Switching power at 400 V (EF009166)	15 kW
Conditioned rated short-circuit current Iq (EF001444)	80 kA
Number of poles (EF001391)	3
Number of auxiliary contacts as normally closed contact (EF001377)	0
Number of auxiliary contacts as normally open contact (EF001376)	0
Number of auxiliary contacts as change-over contact (EF003531)	0
Motor drive....	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-32/I2-RT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.