

INDUSTRIAL COMPONENT DATA

P1-25/I2/SVB/N 207298 Y7-207298 EATON ELECTRIC Main switch, 3 pole + N, 25 A, Emergency-Stop function, Locka..

Brand: EATON - MOELLER | Manufacturer Part Number: P1-25/I2/SVB/N



Manufacturer	EATON - MOELLER
MPN / Reference	P1-25/I2/SVB/N
Catalog number	Y7-207298
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-128F19DD0A
Generated	2026-08-05

Product Overview

Main switch, 3 pole + N, 25 A, Emergency-Stop function, Lockable in the 0 (Off) position, surface mounting

P1-25/I2/SVB/N

Eaton Moeller® series P1 Main switch, P1, 25 A, surface mounting, 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring, Lockable in the 0 (Off) position

Main switch, P1, Rated uninterrupted current (Iu): 25 A, Functions: Interlockable, Emergency switching off function, Fitted with: Red rotary handle and yellow locking ring, Mounting method: Surface mounting, Number of poles: Four-pole, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: NEMA 12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series P1 Main switch Catalog Number 207298 Model Code P1-25/I2/SVB/N EAN

4015082072988 Product Length/Depth 115 mm Product Height 180 mm Product Width 100 mm Product Weight 0.485 kg

Compliances CE Marked Certifications IEC 60947

UL 508

CSA Std. C22.2 No. 14-05

EN 60947-3

VDE

CSA

CSA Class No.: 3211-05
CSA File No.: 012528
IEC/EN 60204
IEC/EN 60947
UL 60947-4-1
UL Category Control No.: NLRV
UL File No.: E36332
VDE 0660
CSA-C22.2 No. 60947-4-1-14
CSA-C22.2 No. 94
CE
IEC/EN 60947-3
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 207298 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
25 A
Rated permanent current at AC-23, 400 V (EF011777)
25 A
Rated permanent current at AC-21, 400 V (EF009165)
25 A
Rated operation power at AC-3, 400 V (EF001364)
7.5 kW
Rated short-time withstand current Icw (EF007050)
0.64 kA
Rated operation power at AC-23, 400 V (EF007027)
13 kW
Switching power at 400 V (EF009166)
13 kW
Conditioned rated short-circuit current Iq (EF001444)

80 kA
Numb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P1-25/I2/SVB/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.