

INDUSTRIAL COMPONENT DATA

T3-2-1/Z/SVA(A) 050984 Y7-50984 EATON ELECTRIC ON-OFF switches, 3 pole, 32 A, Cylinder lock SVA, front plate..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-1/Z/SVA(A)



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-1/Z/SVA(A)
Catalog number	Y7-50984
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-3E635AE9B7
Generated	2026-08-06

Product Overview

ON-OFF switches, 3 pole, 32 A, Cylinder lock SVA, front plate 0-1, 90 °, maintained, rear mounting, P

ON-OFF 3-pole disconnecter switch 32 A SVA cylindrical lock

Eaton Moeller® series T3 ON-OFF switches, T3, 32 A, rear mounting, 3 pole, with black thumb grip and front plate, Cylinder lock SVA

On-Off switch, Product range: Switch with locking mechanism, Part group reference: T3, with black thumb grip and front plate, Information about equipment supplied: with two keys, 3 pole, locking arrangement: Cylinder lock SVA, Notes: Key can only be withdrawn in position 0 (Pos A), Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 On-off switch Catalog Number 050984 Model Code T3-2-1/Z/SVA(A) EAN 4015080509844 Product Length/Depth 178 mm Product Height 73 mm Product Width 61 mm Product Weight 0.233 kg

Certifications IEC/EN 60947-3

IEC/EN 60204

VDE 0660

IEC/EN 60947

ETIM for 050984 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

32 A

Rated permanent current at AC-21, 400 V (EF009165)

32 A

Rated operation power at AC-3, 400 V (EF001364)

11 kW

Rated short-time withstand current I_{cw} (EF007050)

0.65 kA

Rated operation power at AC-23, 400 V (EF007027)

15 kW

Switching power at 400 V (EF009166)

15 kW

Conditioned rated short-circuit current I_q (EF001444)

1 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optional (EF007491)

No

Device construction (EF008240)

Built-in device fixed built-in technique

Suitable for front mo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-1/Z/SVA(A) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.