

INDUSTRIAL COMPONENT DATA

T0-1-15482/IVS 009317 Y7-9317 EATON ELECTRIC ON-OFF switches, Contacts: 2, 20 A, front plate: 0-1, 90 °, mai..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15482/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-15482/IVS
Catalog number	Y7-9317
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-7748EE228E
Generated	2026-08-05

Product Overview

ON-OFF switches, Contacts: 2, 20 A, front plate: 0-1, 90 °, maintained, service distribution board mounting

Disconnect switch ON-OFF; 2-pole; 20a; rating Plate: 0-1; 90 °; Latch; Mounting in control cabinet

ON-OFF switches, T0, 20 A, service distribution board mounting, 1 contact unit(s), Contacts: 2, 90 °, maintained, 0-1, Design number 15482

On-Off switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 90 °, Switching performance: maintained, 1 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On-off switch Catalog Number 009317 Model Code T0-1-15482/IVS EAN 4015080093176 Product Length/Depth 82 mm Product Height 55 mm Product Width 54 mm Product Weight 0.106 kg

Certifications IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

IEC/EN 60947

UL File No.: E36332

CE
CSA
CSA-C22.2 No. 94
VDE 0660
UL 60947-4-1
CSA File No.: 012528
IEC/EN 60204
UL Category Control No.: NLRV
UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 009317 Low-voltage industrial controls and switchgear (EC002611)
Feature Name
Feature Value
Type of switch (EF003496)
On/Off switch
Number of poles (EF001391)
2
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
20 A
Number of switch positions (EF000231)
2
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Device construction (EF008240)
Built-in device
Width in number of modular spacings (EF002950)
4
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
Yes
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
No
Type of control element (EF006976)
Toggle
Front shield size (EF007176)
48x48 mm
Degree of protection (IP), front side (EF003118)
IP30
Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-15482/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.