

INDUSTRIAL COMPONENT DATA

BPZ-KB-11/160 102716 Y7-102716 EATON ELECTRIC Terminal block 4 poles, 160A, 1 input-, 11 output terminals, A..

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-KB-11/160



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-KB-11/160
Catalog number	Y7-102716
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-B7A5EEF7DD
Generated	2026-08-02

Product Overview

Terminal block 4 poles, 160A, 1 input-, 11 output terminals, ALU

BPZ-KB-11/160

Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal block, 4 poles, 160A, 1 input-, 11 output terminals, ALU 4-pole terminal block, BPZ-KB, rated operational current 160 A, mounting on DIN-rail and mounting plate, max. operational voltage 1000 V AC , 1500 VDC. Equipment supplied: 1 4 pole terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic other accessory Catalog Number 102716 Model Code BPZ-KB-11/160 EAN 4015081025763 Product Length/Depth 50.2 mm Product Height 86 mm Product Width 160.4 mm Product Weight 0.706 kg Compliances RoHS conform Certifications IEC 60 947 -7 -1 Delivery program Amperage rating 160 A Number of poles Four-pole Technical data - electrical Voltage rating at AC Cu (IEC) - max 1000 VAC Voltage rating at DC Cu (IEC) - max 1500 VDC Rated peak withstand current 20 kA Rated operation current (Ie) Cu (IEC) 175 A Rated short-time withstand current (Icw) 6.2 kA Technical data - mechanical Mounting method Surface mounting Flush mounting Floor standing distribution board Mounting position Universal Number of clamp positions per pole 12 Number of clamping

units per pole 12 Terminal capacity (single/multi-wire) 2.5 mm² - 16 mm² (outgoing)

6 mm² - 25 mm² (outgoing)

6 mm² - 16 mm² (outgoing, fine wire (with sleeve))

14 - 4 AWG (outgoing)

8 - 2/0 AWG (incoming)

10 - 4 AWG (outgoing)

10 mm² - 25 mm² (incoming, fine wire (with sleeve))

14 - 6 AWG (outgoing, fine wire (with sleeve))

14 - 8 AWG (outgoing, fine wire (with sleeve))

8 - 4 AWG (incoming, fine wire (with sleeve))

10 mm² - 35 mm² (incoming)

2.5 mm² - 10 mm² (outgoing, fine wire (with sleeve)) Conductor cross section (flexible, fine-strand) with cable end sleeve - min 2.5 mm² Conductor cross section (flexible, fine-strand) with cable end sleeve - max 50 mm² Conductor cross section (solid, soli...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-KB-11/160 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.