

INDUSTRIAL COMPONENT DATA

BPZ-KB-11/250 289967 Y7-289967 EATON ELECTRIC Terminal block 1 pole, 250A, 11 output terminals

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-KB-11/250



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-KB-11/250
Catalog number	Y7-289967
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-5E44DE42A3
Generated	2026-08-05

Product Overview

Terminal block 1 pole, 250A, 11 output terminals

BPZ-KB-11/250

Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal block, 1 pole, 250A, 11 output terminals

1-pole terminal block, BPZ-KB, rated operational current 250 A, for copper conductor. Mounting on DIN-rail or mounting plate, UL-listed, makes wiring less time-consuming, ca. 80% less space is required. Module design, 1-pole to 4-pole systems can be assembled by using multiple blocks. Degree of protection IP10, max. operational voltage 1000 V AC , 1500 VDC.

Equipment supplied: 1 1 pole terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic other accessory Catalog Number 289967 Model Code BPZ-KB-11/250 EAN

4015082899677 Product Length/Depth 49 mm Product Height 95.4 mm Product Width 44.5 mm Product Weight 0.477 kg

Compliances RoHS conform Certifications IEC 60 947 -7 -1

UL 1059 Delivery program

Amperage rating 250 A Number of poles Single-pole Technical data - electrical

Voltage rating at AC Cu (CSA) - max 600 VAC Voltage rating at AC Cu (IEC) - max 1000 VAC Voltage rating at AC Cu (UL)

- max 600 VAC Voltage rating at DC Cu (IEC) - max 1500 VDC Rated peak withstand current 51 kA Rated operation current

(Ie) Cu (CSA) 230 A Rated operation current (Ie) Cu (IEC) 250 A Rated operation current (Ie) Cu (UL) 230 A Rated

short-time withstand current (I_{cw}) 21 kA Technical data - mechanical

Mounting method Surface mounting

Floor standing distribution board

Flush mounting Mounting position Universal Number of clamp positions per pole 12 Number of clamping units per pole 12

Terminal capacity (single/multi-wire) 2.5 mm² - 10 mm² (outgoing, fine wire (with sleeve))

2 - 3/0 AWG (incoming, fine wire (with sleeve))

35 mm² - 95 mm² (incoming, fine wire (with sleeve))

14 - 4 AWG (outgoing, fine wire (with sleeve))

2.5 mm² - 16 mm² (outgoing, fine wire (with sleeve))

14 - 2 AWG (outgoing)

16 - 6 AWG (outgoing)

2.5 mm² - 16 mm² (outgoing)

2.5 mm² - 35 mm² (outgoing)

35 mm² - 120 mm² (incoming)

16 - 8 AWG (outgoing)

16 - 8 AWG (outgoing, fine wire (with sleeve))

2 - 4/0 AWG (inc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-KB-11/250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.