

INDUSTRIAL COMPONENT DATA

BPZ-KB-13/125 102719 Y7-102719 EATON ELECTRIC Terminal block 4 poles, 125A

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-KB-13/125



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-KB-13/125
Catalog number	Y7-102719
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-49D66F4C84
Generated	2026-08-02

Product Overview

Terminal block 4 poles, 125A

BPZ-KB-13/125

Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal block, 4 poles, 125A, 13 positions

4-pole terminal block, BPZ-KB, rated operational current 125 A, mounting on DIN-rail and mounting plate, max. operational voltage 690V AC/DC. Equipment supplied: 1 4 pole terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic other accessory Catalog Number 102719 Model Code BPZ-KB-13/125 EAN

4015081025794 Product Length/Depth 48 mm Product Height 93 mm Product Width 126 mm Product Weight 0.396 kg

Compliances RoHS conform Certifications IEC 60 947 -7 -1 Delivery program

Amperage rating 125 A Number of poles Four-pole Technical data - electrical

Voltage rating at AC Cu (IEC) - max 690 VAC Voltage rating at DC Cu (IEC) - max 1500 VDC Rated peak withstand current 29 kA Rated operation current (Ie) Cu (IEC) 125 A Rated short-time withstand current (Icw) 4.2 kA Technical data - mechanical

Mounting method Flush mounting

Floor standing distribution board

Surface mounting Mounting position Universal Number of clamp positions per pole 13 Number of clamping units per pole 14

Terminal capacity (single/multi-wire) 1.5 mm² - 16 mm² (outgoing)

1.5 mm² - 10 mm² (outgoing, fine wire (with sleeve))

1.5 mm² - 25 mm² (outgoing)

1.5 mm² - 16 mm² (outgoing, fine wire (with sleeve))

6 mm² - 25 mm² (incoming, fine wire (with sleeve))

6 mm² - 35 mm² (incoming) Conductor cross section (flexible, fine-strand) with cable end sleeve - min 2.5 mm² Conductor cross section (flexible, fine-strand) with cable end sleeve - max 35 mm² Conductor cross section (solid, solid-strand) - min 2.5 mm² Conductor cross section (solid, solid-strand) - max 35 mm² Clamp material Brass

Plain Torque rating 1.5 Nm Cover/door color Clear (housing body) Housing color Light gray (RAL 7035) Housi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-KB-13/125 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.