

INDUSTRIAL COMPONENT DATA

E58-18DP100-HL 135666 Y7-135666 EATON ELECTRIC Diffuse reflective sensor, Sn 100mm, 4L, 10-30VDC, light, NPN..

Brand: EATON - MOELLER | Manufacturer Part Number: E58-18DP100-HL



Manufacturer	EATON - MOELLER
MPN / Reference	E58-18DP100-HL
Catalog number	Y7-135666
Category	Light scanner with background masking
Minimum order	1 Pcs
Document ID	EO-8F43CA7909
Generated	2026-08-04

Product Overview

Diffuse reflective sensor, Sn=100mm, 4L, 10-30VDC, light, NPN, PNP, M18, metal, line 2m

E58-18DP100-HL

Eaton Moeller® series E58 Diffuse reflective sensor, Sn=100mm, 4L, 10-30VDC, light, NPN, PNP, M18, metal, line 2m

E58 series, product features: sensors with a diameter of 18 mm or 30 mm. Highly refined optics for long sensing ranges and to see through high levels of contamination - unmatched optical performance. Perfect Prox® technology provides exceptional background rejection and extremely high excess gain. Resistant to many chemicals used in the automotive, food processing and forest products industries. Suitable for high temperature , high pressure washdown (82 bar). mechanical Viton gaskets are resistant to extreme temperature variations. Visible sensing beam on all models lets you see where the beam is aimed for quick flush mounting and alignment. The function display is the brightest available and is visible from any angle and in any lighting condition

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series E58 Diffuse reflective sensor Catalog Number 135666 Model Code E58-18DP100-HL

EAN 4015081324590 Product Length/Depth 38.1 mm Product Height 38.1 mm Product Width 38.1 mm Product Weight

0.23 kg Certifications Certified by UL for use in Canada

UL Category Control No.: NRKH, NRKH7

CSA-C22.2 No. 14

UL

UL 508

CSA File No.: UL report applies to both US and Canada

IEC/EN 60947-5-2

CE

UL File No.: E166051 Product specifications

Type Optical sensors Electric connection type Cable Fitted with: Background suppression (Perfect Prox) Enclosure material

Metal Enclosure type Cylinder, screw-thread Operating mode Switching principle: Light switching Explosion safety category

for dust None Explosion safety category for gas None Functions Short-circuit protection

Protection against polarity reversal

Reflected-light beam

Protection against wire breakage Voltage type DC Wire size 22 Connection type 2 m connection cable

4-wire Cable sheath material Polyvinyl chloride (PVC) Light type Other Degree of protection NEMA 6

IP68 Interface type Other LED indicator Status indication of Switching state: Red LED Switch function type Other Load current Max. 250 mA (Ie, NPN)

Max. 100 mA (Ie, PNP) Laser protection class None Operation agent-safety class Safety class 2 Shock resistance 100 g, Mechanical, Shock duration 3 ms Optical surface material Glass Output current (mA) - max 250 mA Output current at protected output - max 0 mA Rated control supply....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E58-18DP100-HL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.