

INDUSTRIAL COMPONENT DATA

E58-30TD250-HLP 135695 Y7-135695 EATON ELECTRIC

Thru-beam photoelectric sensor, receiver, Sn 250m, 4L, 10-30..

Brand: EATON - MOELLER | Manufacturer Part Number: E58-30TD250-HLP



Manufacturer	EATON - MOELLER
MPN / Reference	E58-30TD250-HLP
Catalog number	Y7-135695
Category	Through beam photoelectric sensor
Minimum order	1 Pcs
Document ID	EO-3642E4453E
Generated	2026-08-02

Product Overview

Thru-beam photoelectric sensor, receiver, Sn=250m, 4L, 10-30VDC, light, NPN, PNP, M30, metal
E58-30TD250-HLP

Eaton Moeller® series E58 Thru-beam photoelectric sensor, receiver, Sn=250m, 4L, 10-30VDC, light, NPN, PNP, M30, metal E58-30TD250-HLP

E58 series, product features: sensors with a diameter of 18 mm or 30 mm. Highly refined optics for long sensing ranges and to see through high levels of contamination - unmatched optical performance. Resistant to many chemicals used in the automotive, food processing and forest products industries. Suitable for high temperature , high pressure washdown (82 bar). mechanical Viton gaskets are resistant to extreme temperature variations. visible sensing beam on all models lets you see where the beam is aimed for quick flush mounting and alignment. The function display is the brightest available and is visible from any angle and in any lighting condition. The industry's only background suppression sensors with a 2-wire circuit design. 4-wire DC sensors feature an PNP and a NPN output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series E58 Thru-beam photoelectric sensor Catalog Number 135695 Model Code E58-30TD250-HLP EAN 4015081324880 Product Length/Depth 228.6 mm Product Height 44.45 mm Product Width 165.1

mm Product Weight 0.2 kg Certifications CSA-C22.2 No. 14

CE

UL File No.: E166051

Certified by UL for use in Canada

IEC/EN 60947-5-2

UL

UL 508

UL Category Control No.: NRKH, NRKH7

CSA File No.: UL report applies to both US and Canada Product specifications

Type Optical sensors Device type Receiver Electric connection type Connector M12 Enclosure material Metal Enclosure

type Cylinder, screw-thread Operating mode Switching principle: Light switching Explosion safety category for dust None

Explosion safety category for gas None Functions Short-circuit protection

Protection against polarity reversal

Protection against wire breakage

Detector (for combination with source)

Thru-light beam Voltage type DC Wire size 0 Connection type Plug-in connection M12 x 1

4-wire Cable sheath material Polyvinyl chloride (PVC) Light type Other Degree of protection NEMA 6P

IP68 Interface type Other LED indicator Status indication of Switching state: Red LED Switch function type Other Load

current Max. 100 mA (Ie) Laser protection class None Operation agent-safety class Safety class 2 Shock resistance 100 g,

Mechanical, Shock duration 3 ms Optical surface material Glass Output current (mA) - max 100 mA Output current at

protected output - max 0 mA Rated control supply v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E58-30TD250-HLP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.