

## INDUSTRIAL COMPONENT DATA

## FAK-ATEX 104381 EATON ELECTRIC Option, ATEX type

Brand: EATON - MOELLER | Manufacturer Part Number: FAK-ATEX



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | EATON - MOELLER                   |
| MPN / Reference | FAK-ATEX                          |
| Catalog number  | 104381                            |
| Category        | Foot and palm switch head element |
| Minimum order   | 1 Pcs                             |
| Document ID     | EO-01E74E4C6E                     |
| Generated       | 2026-08-02                        |

## Product Overview

Option, ATEX type

ATEX option; For FAK

ATEX, Description: Only in conjunction with FAK-COMBINATION-\*, For use in accordance with the ATEX directive in dust-laden areas, Zone 22, Category 3, Connection to SmartWire-DT: no, Degree of protection, IEC/EN 60529: None

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

## Additional Product Information

Option, ATEX type Eaton Catalog No. FAK-ATEX ATEX, Description: Only in conjunction with FAK-COMBINATION-\*, For use in accordance with the ATEX directive in dust-laden areas, Zone 22, Category 3, Connection to SmartWire-DT: no, Degree of protection, IEC/EN 60529: None [ Delivery program

Product range Accessories Description Only in conjunction with FAK-COMBINATION-\*

For use in accordance with the ATEX directive in dust-laden areas, Zone 22, Category 3 Approval Connection to SmartWire-DT no , Technical data

General Degree of protection, IEC/EN 60529 None Ambient temperatureOpen -25 - +40 °C , Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C

Operating ambient temperature max. +40 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2

Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of

thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.2  
Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and pa...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAK-ATEX with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.