

INDUSTRIAL COMPONENT DATA

+NA-I2 105866 Y7-105866 EATON ELECTRIC Option, NA type, enclosure I2. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +NA-I2



Manufacturer	EATON - MOELLER
MPN / Reference	+NA-I2
Catalog number	Y7-105866
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-538B8F25F4
Generated	2026-08-04

Product Overview

Option, NA type, enclosure I2. Can only be sold assembled.

+NA-I2

Option, NA type, enclosure I2

Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, center mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Option, NA type, enclosure I2Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, centre mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.Delivery program

Basic functionNA typeFor use withCam switches with UL designNorth American designDesign verification as per IEC/EN

61439

Technical data for design verification
Rated operational current for specified heat dissipation [In] 0 A
Heat dissipation per pole, current-dependent [Pvid] 0 W
Equipment heat dissipation, current-dependent [Pvid] 0 W
Static heat dissipation, non-current-dependent [Pvs] 0 W
Heat dissipation capacity [Pdiss] 0 W
Operating ambient temperature min. -25 °C
Operating ambient temperature max. +40 °C
IEC/EN 61439 design verification
10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.
10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.
10.2 Strength of materials and parts
10.2.3.2 Verification of resistance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NA-I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.