

INDUSTRIAL COMPONENT DATA

FAZT-C10/1N 241027 Y7-241027 EATON ELECTRIC Over current switch, 10A, 1Np, C-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZT-C10/1N



Manufacturer	EATON - MOELLER
MPN / Reference	FAZT-C10/1N
Catalog number	Y7-241027
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-A6F056CB18
Generated	2026-08-05

Product Overview

Over current switch, 10A, 1Np, C-Char, AC

FAZT-C10/1N

Miniature circuit breaker (MCB), 10 A, 1p+N, characteristic: C

Miniature circuit breaker (MCB), FAZ-T, 1-pole+N, tripping characteristic: C, rated current In: 10 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

Miniature circuit breaker (MCB), 10 A, 1p+N, characteristic: CMiniature circuit breaker (MCB), FAZ-T, 1-pole+N, tripping characteristic: C, rated current In: 10 A, Switchgear for industrial and advanced commercial applications

General specificationsProduct nameEaton Moeller series xEffect - FAZ-T MCBPart

no.FAZT-C10/1NEAN4015082410278Product Length/Depth80 millimetreProduct height75.5 millimetreProduct width36

millimetreProduct weight0.198 kilogramCompliancesRoHS conformCertificationsIEC/EN 60947-2

EN45545-2

IEC 61373Product TradenamexEffect - FAZ-TProduct TypeMCBProduct Sub TypeNoneDelivery

programApplicationSwitchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applicationsNumber of polesSingle-pole + NNumber of poles

(total)2Number of poles (protected)1Tripping characteristicCRelease characteristicCAMperage Rating10 ATypeFAZ-T

Miniature circuit breakerTechnical Data - ElectricalVoltage typeACVoltage rating (IEC/EN 60898-1)240 V ACVoltage rating

(IEC/EN 60947-2)240 V AC Rated operational voltage (Ue) - max230 V Operational voltage (IEC/EN 60947-2) - max254 V
AC Operational voltage at DC (EC/EN 60947-2) - max60 V DC Rated insulation voltage (Ui)440 V Rated impulse withstand
voltage (Uimp)4 kV Frequency rating50 Hz / 60 Hz Frequency rating - min50 Hz Frequency rating - max60 Hz Rated switching
capacity (IEC/EN 60947-2) at max voltage rating15 kA Rated switching capacity (IEC/EN 60947-2)25 kA Rated switching
capacity (I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZT-C10/1N with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.