

INDUSTRIAL COMPONENT DATA

FAZ-B10/1-DC 176067 Y7-176067 EATON ELECTRIC Miniature circuit breaker (MCB), 10A, 1p, type B characteristic..

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-B10/1-DC



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-B10/1-DC
Catalog number	Y7-176067
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-7C15170662
Generated	2026-08-03

Product Overview

Miniature circuit breaker (MCB), 10A, 1p, type B characteristic, DC

Small circuit breaker

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 10 A, 1p, characteristic: B, DC
Miniature circuit breaker (MCB), FAZ-DC, 1-pole, tripping characteristic: B, rated current In: 10 A, rated switching capacity (IEC/EN 60947-2): 10 kA, Switchgear for DC applications

General specifications
Product nameEaton Moeller series xEffect - FAZ-DC MCB
Part no.FAZ-B10/1-DC
EAN4015081712632
Product Length/Depth80 millimetre
Product height75.5 millimetre
Product width17.7 millimetre
Product weight0.11 kilogram
ComplianceRoHS conform
CertificationsEN45545-2
IEC 61373
Product TradenamexEffect - FAZ-DC
Product TypeMCB
Product Sub TypeNone
Delivery programApplicationSwitchgear for DC applications
Number of polesSingle-pole
Number of poles (total)1
Number of poles (protected)1
Tripping characteristicB
Release characteristicB
Amperage Rating10 A
TypeFAZ-DC

Miniature circuit breaker
Technical Data - Electrical
Voltage typeDC
Rated operational voltage (Ue) - max250 V
Rated insulation voltage (Ui)440 V
Rated impulse withstand voltage (Uimp)4 kV
Frequency rating - min50 Hz
Frequency rating - max60 Hz
Rated switching capacity (IEC/EN 60947-2)10 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V0 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V10 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V10 kA
Overvoltage categoryII
Pollution degree2

Technical Data - Mechanical
Width in number of modular spacings1
Built-in depth70.5 mm
Degree of

protectionIP20Connec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-B10/1-DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.