

INDUSTRIAL COMPONENT DATA

PLSM-C13/2-MW 242403 Y7-242403 EATON ELECTRIC Over current switch, 13A, 2p, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: PLSM-C13/2-MW



Manufacturer	EATON - MOELLER
MPN / Reference	PLSM-C13/2-MW
Catalog number	Y7-242403
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-94A3EF33B2
Generated	2026-08-04

Product Overview

Over current switch, 13A, 2p, type C characteristic

PLSM-C13/2-MW

Miniature circuit breaker (MCB), 13 A, 2p, characteristic: C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

Miniature circuit breaker (MCB), 13 A, 2p, characteristic: C
Miniature circuit breaker (MCB), PLSM, 2-pole, tripping characteristic: C, rated current I_n : 13 A, rated switching capacity according to IEC/EN 60898-1: 10 kA, Switchgear for residential and commercial applications

General specifications
Product name Eaton Moeller series xPole - PLS6/M MCB
Part no. PLSM-C13/2-MW
EAN 4015082424039

Product Length/Depth 80 millimetre
Product height 75 millimetre
Product width 35 millimetre
Product weight 0.21 kilogram

Compliance RoHS conform
Product Trade name xPole - PLS6/M
Product Type MCB
Product Sub Type None

Delivery program Application Switchgear for residential and commercial applications

xPole - Switchgear for residential and commercial applications
Number of poles Two-pole
Number of poles (total) 2
Number of poles (protected) 2
Tripping characteristic C
Release characteristic CA
Mperage Rating 13 A
Type Miniature circuit breaker

PLSM
Technical Data - Electrical
Voltage type AC
Rated operational voltage (U_e) - max 400 V
Rated insulation voltage (U_i) 440 V
Rated impulse withstand voltage (U_{imp}) 4 kV
Frequency rating - min 50 Hz
Frequency rating - max 60 Hz
Rated switching capacity (IEC/EN 60898-1) 10 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V 10 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V 10 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 0 kA
Rated short-circuit

breaking capacity (IEC 60947-2) at 400 V0 kAOvervoltage categoryIIIPollution degree2Technical Data - MechanicalWidth in number....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PLSM-C13/2-MW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.