

INDUSTRIAL COMPONENT DATA

FAZ-D13/3-NA 102268 Y7-102268 EATON ELECTRIC Miniature circuit breaker (MCB), 13A, 3p, D-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D13/3-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D13/3-NA
Catalog number	Y7-102268
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-CB02FC29C9
Generated	2026-08-04

Product Overview

Miniature circuit breaker (MCB), 13A, 3p, D-Char, AC

FAZ-D13/3-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 3-pole, tripping characteristic: D, rated current In: 13 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 3-pole, tripping characteristic: D, rated current In: 13 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102268 Model Code FAZ-D13/3-NA
EAN 4015081021444 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 53.1 mm Product Weight
0.364 kg Compliances RoHS conform Certifications UL 489

CSA-C22.2 No. 5-09

CSA (Class No. 1432-01)

UL 489, CSA C22.2 No. 5

UL (File No. E235139)

CE marking

Specially designed for North America, suitable as BCPD

CSA (File No. 204453)

North America (UL listed, CSA certified)

IEC 60947-2

IEC/EN 60947-2

UL (Category Control Number DIVQ)

EN45545-2

IEC 61373 Delivery program

Application Number of poles Three-pole Number of poles (total) 3 Number of poles (protected) 3 Tripping characteristic D

Release characteristic D Amperage Rating 13 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 415 V

Voltage rating (UL) 480Y/277 V Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated

impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching

capacity (IEC/EN 60947-2) 15 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated short-circuit

breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA Rated

short-circuit breaking capacity (IEC 60947-2) at 400 V 15 kA Selectivity class....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D13/3-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.