

INDUSTRIAL COMPONENT DATA

FAZ-D15/3-NA 102269 Y7-102269 EATON ELECTRIC Miniature circuit breaker (MCB), 15A, 3p, D-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D15/3-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-D15/3-NA
Catalog number	Y7-102269
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-69C925AEFF
Generated	2026-08-05

Product Overview

Miniature circuit breaker (MCB), 15A, 3p, D-Char, AC

FAZ-D15/3-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 3-pole, tripping characteristic: D, rated current In: 15 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 3-pole, tripping characteristic: D, rated current In: 15 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102269 Model Code FAZ-D15/3-NA
EAN 4015081021451 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 53.1 mm Product Weight
0.365 kg Compliances RoHS conform Certifications UL (File No. E235139)

CSA (File No. 204453)

CE marking

Specially designed for North America, suitable as BCPD

CSA (Class No. 1432-01)

UL 489, CSA C22.2 No. 5

IEC 60947-2

UL 489

CSA-C22.2 No. 5-09

IEC/EN 60947-2

UL (Category Control Number DIVQ)

North America (UL listed, CSA certified)

EN45545-2

IEC 61373 Delivery program

Application Number of poles Three-pole Number of poles (total) 3 Number of poles (protected) 3 Tripping characteristic D

Release characteristic D Amperage Rating 15 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 415 V

Voltage rating (UL) 480Y/277 V Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated

impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching

capacity (IEC/EN 60947-2) 15 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated short-circuit

breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA Rated

short-circuit breaking capacity (IEC 60947-2) at 400 V 15 kA Selectivity class....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D15/3-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.