

INDUSTRIAL COMPONENT DATA

FAZ-C2,5/2 278749 Y7-278749 EATON ELECTRIC Miniature circuit breaker (MCB), 2.5A, 2p, type C characteristic

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C2,5/2



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C2,5/2
Catalog number	Y7-278749
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-7435F5C8EF
Generated	2026-08-04

Product Overview

Miniature circuit breaker (MCB), 2.5A, 2p, type C characteristic

FAZ-C2,5/2

Eaton Moeller series xEffect - FAZ MCB. FAZ, 2-pole, tripping characteristic: C, rated current In: 2.5 A

Miniature circuit breaker (MCB), FAZ, 2-pole, tripping characteristic: C, rated current In: 2.5 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ MCB Catalog Number 278749 Model Code FAZ-C2,5/2 EAN

4015082787493 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 36 mm Product Weight 0.225 kg

Compliances UL CSA09 (with supplementary protector only)

RoHS conform Certifications UL (File No. E177451)

IEC/EN 60898

CSA (Class No. 3215-30)

UL 1077

CE marking

CSA-C22.2 No. 235

IEC/EN 60947-2

CSA (File No. 204453)

UL (Category Control Number QVNU2, QVNU8)

North America (UL recognized, CSA certified)

EN45545-2

IEC 61373 Delivery Programme

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic C

Release characteristic C Amperage Rating 2.5 A Type FAZ

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC / 415 V AC Voltage rating (IEC/EN 60898-1) 415 VAC Voltage rating (UL)

480Y/277 V Voltage rating (UL CSA 13) 480 Y/277 V AC; 96 V DC Rated operational voltage (Ue) - max 400 V Operational voltage (IEC/EN 60947-2) - max 440 VAC Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV

Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) at max voltage rating 10 kA Rated switching capacity (IEC/EN 60947-2) 15 kA Rated switching capacity (IEC/EN 60898-1) 10 kA Breaking capacity 10 kA (UL1077) Rated service short-circuit breaking capacity (IEC/EN 60898-1) 7.5 kA Rated service short-c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C2,5/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.