

INDUSTRIAL COMPONENT DATA

AZ-3N-B25 174520 Y7-174520 EATON ELECTRIC Miniature circuit breaker (MCB), 25A, 3pole+N, type B characterist..

Brand: EATON - MOELLER | Manufacturer Part Number: AZ-3N-B25



Manufacturer	EATON - MOELLER
MPN / Reference	AZ-3N-B25
Catalog number	Y7-174520
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-A07E710C2E
Generated	2026-08-04

Product Overview

Miniature circuit breaker (MCB), 25A, 3pole+N, type B characteristic

AZ-3N-B25

Eaton Moeller series xEffect - AZ MCB. Miniature circuit breaker (MCB), 25A, 3pole+N, type B characteristic

Miniature circuit breaker (MCB) AZ, 3 pole+N, Tripping Characteristic: B, Rated current In: 25 A, Rated switching capacity (IEC/EN 60947-2): 25 kA, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - AZ MCB Catalog Number 174520 Model Code AZ-3N-B25 EAN

4015081709762 Product Length/Depth 75 mm Product Height 90 mm Product Width 108 mm Product Weight 0.842 kg

Compliances RoHS conform Certifications EN45545-2

IEC 61373 Delivery programme

Application Number of poles Three-pole + N Number of poles (total) 4 Number of poles (protected) 3 Tripping characteristic

B Release characteristic B Amperage Rating 25 A Type AZ

Miniature circuit breaker

Technical data - electrical

Voltage type AC Rated operational voltage (Ue) - max 400 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN

60947-2) 25 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 25 kA Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 25 kA Overvoltage category III Pollution degree 2 Technical data - mechanical Width in number of modular spacings 6 Built-in depth 75 mm Degree of protection IP20 Connectable conductor cross section (solid-core) - min 2.5 mm² Connectable conductor cross section (solid-core) - max 50 mm² Connectable conductor cross section (multi-wired) - min 2.5 mm² Connectable conductor cross section (multi-wired) - max 50 mm² Design verification as per IEC/EN 61439 - tec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / AZ-3N-B25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.