

INDUSTRIAL COMPONENT DATA

FAZ-C2/2-DC 279134 Y7-279134 EATON ELECTRIC Over current switch, 2A, 2p, C-Char, DC current

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C2/2-DC



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C2/2-DC
Catalog number	Y7-279134
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-2CA3466527
Generated	2026-08-04

Product Overview

Over current switch, 2A, 2p, C-Char, DC current

FAZ-C2/2-DC

Eaton Moeller series xEffect - FAZ-DC MCB. FAZ-DC, 2-pole, tripping characteristic: C, rated current In: 2 A, Switchgear for DC applications

Miniature circuit breaker (MCB), FAZ-DC, 2-pole, tripping characteristic: C, rated current In: 2 A, Switchgear for DC applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-DC MCB Catalog Number 279134 Model Code FAZ-C2/2-DC EAN 4015082791346 Product Length/Depth 80 mm Product Height 75.5 mm Product Width 36 mm Product Weight 0.226 kg
Compliances RoHS conform Certifications CSA Std. C22.2 No. 235

UL 1077

IEC/EN 60947-2

EN45545-2

IEC 61373 Catalog Notes Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices. Delivery program

Application Switchgear for DC applications Number of poles Two-pole Number of poles (total) 2 Number of poles

(protected) 2 Tripping characteristic C Release characteristic C Amperage Rating 2 A Type Technical data - electrical
Voltage type DC Voltage rating at DC 250 V DC (per pole) Rated operational voltage (Ue) - max 250 V Rated insulation
voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60
Hz Rated switching capacity (IEC/EN 60947-2) 10 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated
short-circuit breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 10 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 10 kA Admissible back-up fuse - max 100 A gL/gG Selectivity
class 3 Overvoltage category III Pollution degree 2 Lifespan, electrical 10000 operations Direction of incoming supply
Polarity dependent Technical data - mechanical
Frame 45 mm Enclosure w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C2/2-DC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.