

INDUSTRIAL COMPONENT DATA

FAZ-Z2/4 279109 Y7-279109 EATON ELECTRIC Over current switch, 2A, 4p, Z-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-Z2/4



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-Z2/4
Catalog number	Y7-279109
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-356EB63E83
Generated	2026-08-05

Product Overview

Over current switch, 2A, 4p, Z-Char, AC

FAZ-Z2/4

Miniature circuit breaker (MCB), 2 A, 4p, characteristic: Z

Miniature circuit breaker (MCB), FAZ, 4 pole, tripping characteristic: Z, rated current In: 2 A, Switchgear for industrial and advanced commercial applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Miniature circuit breaker (MCB), 2 A, 4p, characteristic: Z
Miniature circuit breaker (MCB), FAZ, 4 pole, tripping characteristic: Z, rated current In: 2 A, Switchgear for industrial and advanced commercial applications

General specifications
Product name Eaton Moeller series xEffect - FAZ MCB
Part no. FAZ-Z2/4
EAN 4015082791094
Product Length/Depth 80 millimetre
Product height 75.5 millimetre
Product width 72 millimetre
Product weight 0.453 kilogram
Compliances RoHS conform
Certifications IEC/EN 60898

IEC/EN 60947-2

EN 45545-2

IEC 61373
Product Tradename xEffect - FAZ
Product Type MCB
Product Sub Type None
Delivery program Application Switchgear for industrial and advanced commercial applications

xEffect - Switchgear for industrial and advanced commercial applications
Number of poles Four-pole
Number of poles (total) 4
Number of poles (protected) 4
Tripping characteristic Z
Release characteristic Z
Amperage Rating 2 A
Type FAZ

Miniature circuit breaker
Technical Data - Electrical
Voltage type AC
Voltage rating 240 V AC / 415 V AC
Voltage rating at DC 60 V DC (per pole)
Rated operational voltage (Ue) - max 400 V
Rated insulation voltage (Ui) 440 V
Rated impulse withstand voltage (Uimp) 4 kV
Frequency rating - min 50 Hz
Frequency rating - max 60 Hz
Rated switching capacity (IEC/EN 60947-2) 10 kA
Operational switching capacity 7.5 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 10 kA
Rated short-circuit bre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-Z2/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.