

INDUSTRIAL COMPONENT DATA

FAZ-C32/1-NA 102094 Y7-102094 EATON ELECTRIC Over current switch, 32A, 1p, C-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C32/1-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C32/1-NA
Catalog number	Y7-102094
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-E08A56E488
Generated	2026-08-05

Product Overview

Over current switch, 32A, 1p, C-Char, AC

FAZ-C32/1-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 1-pole, tripping characteristic: C, rated current In: 32 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 1-pole, tripping characteristic: C, rated current In: 32 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102094 Model Code FAZ-C32/1-NA
EAN 4015081019700 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 17.7 mm Product Weight
0.128 kg Compliances RoHS conform Certifications CSA (File No. 204453)

North America (UL listed, CSA certified)

Specially designed for North America, suitable as BCPD

UL (File No. E235139)

IEC 60947-2

UL 489

CSA-C22.2 No. 5-09

UL (Category Control Number DIVQ)

CE marking

IEC/EN 60947-2

UL 489, CSA C22.2 No. 5

CSA (Class No. 1432-01)

IEC 61373

EN45545-2 Delivery program

Application Number of poles Single-pole Number of poles (total) 1 Number of poles (protected) 1 Tripping characteristic C

Release characteristic C Amperage Rating 32 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 277 V AC / 480 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 254 V

Voltage rating (UL) 277 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 440 V Rated impulse

withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity

(IEC/EN 60947-2) 15 kA Breaking capacity 10 kA (UL489) Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA

Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230

V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at 40...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C32/1-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.