

## INDUSTRIAL COMPONENT DATA

# FAZ-D35/1-NA 102115 Y7-102115 EATON ELECTRIC Miniature circuit breaker (MCB), 35A, 1p, D-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D35/1-NA



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | EATON - MOELLER                 |
| MPN / Reference | FAZ-D35/1-NA                    |
| Catalog number  | Y7-102115                       |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-0A83E80E7D                   |
| Generated       | 2026-08-04                      |

## Product Overview

Miniature circuit breaker (MCB), 35A, 1p, D-Char, AC

FAZ-D35/1-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 1-pole, tripping characteristic: D, rated current In: 35 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 1-pole, tripping characteristic: D, rated current In: 35 A, Switchgear for export to North America (UL-listed)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                   |
|--------------|---------------------------------------------------|
| Catalog path | EATON - MOELLER > Modular Switchgear - Industrial |
|--------------|---------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102115 Model Code FAZ-D35/1-NA  
EAN 4015081019915 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 17.7 mm Product Weight  
0.127 kg Compliances RoHS conform Certifications North America (UL listed, CSA certified)

CE marking

IEC/EN 60947-2

CSA-C22.2 No. 5-09

UL (File No. E235139)

IEC 60947-2

UL (Category Control Number DIVQ)

CSA (Class No. 1432-01)

UL 489

CSA (File No. 204453)

UL 489, CSA C22.2 No. 5

Specially designed for North America, suitable as BCPD

EN45545-2

IEC 61373 Delivery program

Application Number of poles Single-pole Number of poles (total) 1 Number of poles (protected) 1 Tripping characteristic D

Release characteristic D Amperage Rating 35 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 240 V AC / 415 V  
AC Voltage rating (UL) 240 V Rated operational voltage (Ue) - max 240 V Rated insulation voltage (Ui) 440 V Rated  
impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching  
capacity (IEC/EN 60947-2) 15 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated short-circuit  
breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA Rated  
short-circuit breaking capacity (IEC 60947-2) at 400 V 15 kA Selectivity class 3...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D35/1-NA with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.