

## INDUSTRIAL COMPONENT DATA

# FAZ-D35/2-NA 102195 Y7-102195 EATON ELECTRIC Miniature circuit breaker (MCB), 35A, 2p, D-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-D35/2-NA



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | EATON - MOELLER                 |
| MPN / Reference | FAZ-D35/2-NA                    |
| Catalog number  | Y7-102195                       |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-0057D9E115                   |
| Generated       | 2026-08-05                      |

## Product Overview

Miniature circuit breaker (MCB), 35A, 2p, D-Char, AC

FAZ-D35/2-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 2-pole, tripping characteristic: D, rated current In: 35 A, Switchgear for export to North America (UL-listed)

Miniature circuit breaker (MCB), FAZ-NA, 2-pole, tripping characteristic: D, rated current In: 35 A, Switchgear for export to North America (UL-listed)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                   |
|--------------|---------------------------------------------------|
| Catalog path | EATON - MOELLER > Modular Switchgear - Industrial |
|--------------|---------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102195 Model Code FAZ-D35/2-NA  
EAN 4015081020713 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 35.4 mm Product Weight  
0.254 kg Compliances RoHS conform Certifications CSA (File No. 204453)

CSA (Class No. 1432-01)

IEC 60947-2

CSA-C22.2 No. 5-09

UL 489, CSA C22.2 No. 5

IEC/EN 60947-2

UL 489

UL (File No. E235139)

North America (UL listed, CSA certified)

CE marking

UL (Category Control Number DIVQ)

Specially designed for North America, suitable as BCPD

EN45545-2

IEC 61373 Delivery program

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic D

Release characteristic D Amperage Rating 35 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 415 V Voltage rating (UL) 240 V Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 15 kA Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 15 kA Selectivity class 3 Overvoltage cate...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-D35/2-NA with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.