


INDUSTRIAL COMPONENT DATA

FAZ-C40/2-NA 102176 Y7-102176 EATON ELECTRIC Over current switch, 40A, 2p, C-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: FAZ-C40/2-NA



Manufacturer	EATON - MOELLER
MPN / Reference	FAZ-C40/2-NA
Catalog number	Y7-102176
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-11C00BBA0A
Generated	2026-08-05

Product Overview

Over current switch, 40A, 2p, C-Char, AC

FAZ-C40/2-NA

Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB. FAZ-NA, 2-pole, tripping characteristic: C, rated current In: 40 A, Switchgear for export to North America (UL-listed)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller series xEffect - FAZ-NA, FAZ-RT MCB Catalog Number 102176 Model Code FAZ-C40/2-NA

EAN 4015081020522 Product Length/Depth 105 mm Product Height 75.5 mm Product Width 35.4 mm Product Weight

0.254 kg Compliances RoHS conform Certifications CE marking

UL (Category Control Number DIVQ)

IEC 60947-2

CSA (File No. 204453)

UL 489, CSA C22.2 No. 5

UL (File No. E235139)

Specially designed for North America, suitable as BCPD

UL 489

North America (UL listed, CSA certified)

CSA-C22.2 No. 5-09

CSA (Class No. 1432-01)

IEC/EN 60947-2

EN45545-2

IEC 61373 Delivery program

Application Number of poles Two-pole Number of poles (total) 2 Number of poles (protected) 2 Tripping characteristic C

Release characteristic C Amperage Rating 40 A Type FAZ-NA

Miniature circuit breaker

Technical data - electrical

Voltage type AC Voltage rating 240 V AC Voltage rating at DC 60 V DC Voltage rating (IEC/EN 60947-2) 440 V Voltage rating (UL) 240 V Rated operational voltage (Ue) - max 415 V Rated insulation voltage (Ui) 440 V Rated impulse withstand voltage (Uimp) 4 kV Frequency rating - min 50 Hz Frequency rating - max 60 Hz Rated switching capacity (IEC/EN 60947-2) 15 kA Breaking capacity 10 kA (UL489) Rated short-circuit breaking capacity (EN 60898) at 230 V 0 kA Rated short-circuit breaking capacity (EN 60898) at 400 V 0 kA Rated short-circuit breaking capacity (IEC 60947-2) at 230 V 15 kA Rated short-circuit breaking capacity (IEC 60947-2) at 400 V 15 kA Sele...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FAZ-C40/2-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.